



## **Description**

The dimensions are established for every project.

The self-supporting structure, dismountable, made of galvanized steel with exterior sandwich panels painted on the outside in electrostatic field with RAL 9006 and an insulating interlayer.

Self-supporting sandwich panels painted exterior

Roof made of sandwich panels ( prefabricated type in layers self-supporting with total adhesion between the components . Polyurethane provides very good hydro, thermal and acoustic insulation , with a 5 % sloap from the front to the back ;

With two door access to the work area, constructed of PVC profile . Shutters in the sales area are made of profiles and panels supported by air springs provided with mechanical anti lock systems;

Interior walls and ceiling are plated (  $\mbox{paneled}$  ) with stainless steel sheets;

Sandwich floor protected by aluminum antislip sheets;

General lighting is on the ceiling (fluorescent lamps) .

Indoor wall mounted heat convectors;

Hood extractor fans are positioned on the roof, the chimney will exceed the attic of the adjacent building;

On request we can make a (fence) on three sides behind the serving stand .

On request can be done and fencing (fence) on three sides of the back bench serving, with an access door windows profiles of PVC.Imprejmuirea made self-supporting construction, demountable poles galvanized steel profiles and plated panels lisa galvanized powder coated, RAL 9006;

Note: The foundation, utility services (electricity 220V and 380 V, water, sewer) up to and from the location, location permits and licenses and site supervision are the Employer tasks.

All documents that accompany this presentation are the intellectual property of SC INOX S. A.

1 / 1